

Request for Proposal (RFP) for Design, Supply, Installation, Integration, Testing and Commissioning of a comprehensive on-premise Audio Video (AV) Solution for StockHolding Corporation of India Ltd at Mahape and Centre Point Offices in Mumbai

Sr. No.	Page No.	Description	Existing Clause	Amended Clause																								
1	20	Scope of Work 5. Room-Wise Solution and Bill of Materials (BOM) has to be provided by the bidder	<table><tr><th colspan="3">BOQ - Board Room - Lower Parel :</th></tr><tr><th>Sr. No.</th><th>Description</th><th>Qty</th></tr><tr><td>2.1</td><td>85" Display</td><td>1</td></tr><tr><td>2.2</td><td>55" Display</td><td>2</td></tr></table>	BOQ - Board Room - Lower Parel :			Sr. No.	Description	Qty	2.1	85" Display	1	2.2	55" Display	2	<table><tr><th colspan="3">BOQ - Board Room - Lower Parel :</th></tr><tr><th>Sr. No.</th><th>Description</th><th>Qty</th></tr><tr><td>2.1</td><td>98" Display</td><td>1</td></tr><tr><td>2.2</td><td>65" Display</td><td>2</td></tr></table>	BOQ - Board Room - Lower Parel :			Sr. No.	Description	Qty	2.1	98" Display	1	2.2	65" Display	2
BOQ - Board Room - Lower Parel :																												
Sr. No.	Description	Qty																										
2.1	85" Display	1																										
2.2	55" Display	2																										
BOQ - Board Room - Lower Parel :																												
Sr. No.	Description	Qty																										
2.1	98" Display	1																										
2.2	65" Display	2																										
2	36	Technical Specifications For Board rooms 5. Video and Audio Inputs	1 x HDMI/HDCI/USB input for connecting main 4K Camera 1 x HDMI input to share 4K/Full HD content from PC/Laptop/Document camera/PTZ Camera. It should have additional USB port for connecting minimum 2 more cameras or it should support AV over IP to connect multiple cameras. It should support minimum 6 digital omnidirectional mics. The bidder needs to quote 3 digital omnidirectional microphones with mute/unmute soft touch button on the microphone. Each microphone should have at least 15 feet pickup range. 1 x RCA/3.5mm stereo line-in	1 x HDMI/HDCI/USB input for connecting main 4K Camera 1 x HDMI input to share 4K/Full HD content from PC/Laptop/Document camera/PTZ Camera. It should have additional USB port for connecting minimum 2 more cameras or it should support AV over IP to connect multiple cameras. It should support minimum 6 digital omnidirectional mics. The bidder needs to quote 4 digital omnidirectional microphones with mute/unmute soft touch button on the microphone. Each microphone should have at least 15 feet pickup range. 1 x RCA/3.5mm stereo line-in																								
3	42 and 43	Specifications for 98 and 85 inch display	-	Added (refer Addendum 01 - CPCM-27/2026-27 in this document)																								
4	39	Specification for 50 inch display	-	Removed																								
5	3	Last Date for Submission of Online Bid	11-Aug-2026 04:00 PM	13-Aug-2026 11:00 AM																								
6	3	Date of opening bid	11-Aug-2026 04:30 PM	13-Aug-2026 11:30 AM																								

Note: All other clauses/Terms & conditions except above shall remain same as per RFP (RFP Reference Number: CPCM-27/2026-27)

**Request for Proposal (RFP) for Design, Supply, Installation, Integration, Testing and Commissioning of a comprehensive on-premise Audio Video (AV)
Solution for StockHolding Corporation of India Ltd at Mahape and Centre Point Offices in Mumbai**

Sr. No.	Page No.	Description	Additional Clause			
1	42		Sr. No.	Description	98-inch Display	Compliance (Y/N)
			1	Screen Size	98 inches	
			2	Technology	Mini LED / QLED / QD-Mini LED	
			3	Native Resolution (Pixels)	3840 × 2160 (4K UHD)	
			4	Aspect Ratio	16:09	
			5	Brightness	~1000–1500 nits	
			6	Native Contrast Ratio (Minimum)	5000:1 – 7000:1	
			7	Viewing Angle (Horizontal: Vertical)	178° : 178°	
			8	Response Time (G to G)	6–8 ms	
			9	Orientation	Landscape / Portrait	
			10	Haze	2–3% (anti-glare coating)	
			11	Speaker	30–60 W, Dolby Atmos	
			12	MTBF	≥ 50,000 hours	
			13	Operating System (OEM)	Proprietary Smart OS (Tizen / Google TV/Web OS/Android etc.,)	
			14	HDMI (2.0 / 2.1)	Minimum 03 ports	
			15	USB 2.0 Port	Minimum 02 ports	
			16	LAN RJ45 (Required)	Yes	
			17	External Control	RS232 / IP / IR	
			18	Wi-Fi	Wi-Fi 5/6	
			19	Web Browser	Integrated	
			20	Media Player	Built-in	
			21	Built-in Storage	16–32 GB	
			22	Signage Software	OEM CMS (MagicINFO / Android signage)	
			23	Duty Cycle	16/7 – 24/7	
			24	IP Rating	IP5X (dust protection)	
			25	Mounting Arrangement	Wall mount / Stand	
			26	Certifications	BIS, BEE, Energy Star, RoHS, CE, UL, ISO	

			27	Power Consumption Typical [W/h]	350–450 W	
			28	Operating Temperature Range (°C)	0 – 40 °C	
			29	Operating Humidity (%RH)	10 – 80%	
			30	Accessories	Power cord, HDMI and other cables, remote control, user manual, Swivel mount bracket	
			31	On-Site OEM Warranty (Years)	03 years	
			32	Swivel Mount	Pivot left or right (usually 30°–90° each way), must be heavy-duty, supporting ~60–70 kg safely	
2	43		S.No	Description	85-inch Display	Compliance (Y/N)
			1	Screen Size	85 inches	
			2	Technology	Mini LED / QLED	
			3	Native Resolution (Pixels)	3840 × 2160 (4K UHD)	
			4	Aspect Ratio	16:09	
			5	Brightness	~800–1500 nits	
			6	Native Contrast Ratio (Minimum)	4000:1 – 6000:1	
			7	Viewing Angle (Horizontal: Vertical)	178° : 178°	
			8	Response Time (G to G)	6–8 ms	
			9	Orientation	Landscape / Portrait	
			10	Haze	2–3% (anti-glare coating)	
			11	Speaker	30–80 W, Dolby Atmos	
			12	MTBF	≥ 50,000 hours	
			13	Operating System (OEM)	Proprietary Smart OS (Tizen / Google TV/Web OS/Android etc..)	
			14	HDMI (2.0 / 2.1)	Minimum 03 ports	
			15	USB 2.0 Port	Minimum 02 ports	
			16	LAN RJ45 (Required)	Yes	
			17	External Control	RS232 / IP / IR	
			18	Wi-Fi	Wi-Fi 5/6	
			19	Web Browser	Integrated	

			20	Media Player	Built-in	
			21	Built-in Storage	16–32 GB	
			22	Signage Software	OEM CMS (MagicINFO / Android signage)	
			23	Duty Cycle	16/7 – 24/7	
			24	IP Rating	IP5X (dust protection)	
			25	Mounting Arrangement	Wall mount / Stand	
			26	Certifications	BIS, BEE, Energy Star, RoHS, CE, UL, ISO	
			27	Power Consumption Typical [W/h]	250–350 W	
			28	Operating Temperature Range (°C)	0 – 40 °C	
			29	Operating Humidity (%RH)	10 – 80%	
			30	Accessories	Power cord, HDMI and other cables, remote control, user manual, Swivel mount bracket	
			31	On-Site OEM Warranty (Years)	03 years	
			32	Swivel Mount	Pivot left or right (usually 30°–90° each way), must be heavy-duty, supporting ~45-50 kg safely	